


### GI Flexible Conduit



- material : hot-dip galvanized
- standard : UL1
- Galvanized steel core
- High flexibility
- Electromagnetic interference screen system
- Superior mechanical, abrasion and wear performance
- For hazardous area Class 3 Division 1,2
- UL1 standard
- UL Listed

#### Technical Details



IP40	-30 C	+300 C
------	-------	--------

Product Code	Size I	A	B	C	D	E	F	Net Weight (kg/m)	In Pack (m)
BD008	5/16"	8.00	12.50	2.25	44.00				30.00
BD010	3/8"	10.00	15.00	2.50	50.00			0,215	30.00
BD016	1/2"	16.00	23.00	3.50	75.00			0,401	30.00
BD021	3/4"	21.00	28.00	3.50	100.00			0,526	30.00
BD026	1"	26.00	35.00	4.50	125.00			0,806	30.00
BD035	1 1/4"	32.00	41.00	4.50	160.00			0,961	20.00
BD040	1 1/2"	40.00	49.00	4.50	190.00			1,187	20.00
BD052	2"	52.00	62.00	5.00	255.00			1,139	15.00
BD063	2 1/2"	63.00	78.00	7.50	310.00				15.00
BD078	3"	76.00	90.00	7.50	375.00				15.00
BD102	4"	102.00	116.00	7.50	500.00				15.00