




FLEXIBLE CONDUIT, STEEL, LIQUID-TIGHT GRAY UL LISTED

- material : hot-dip galvanized
- standard : UL360
- Liquid-Tight Flexible conduit of Hot-dipped galvanized steel strip wound with plain PVC oversheath
- Self-extinguishing
- High resistance to abrasion, diluted acids, oils, electrical insulation
- Superior mechanical, abrasion and wear performance
- Size 3/8" through 4" must be installed with a separate ground wire
- Oil-resistant, flame retardant, and sunlight (ultraviolet, UV) resistant
- Compression strength : 1250N
- Impact strength : 6J
- RoHS, REACH and UL 360 compliant PVC jacketed
- UL Listed
- Color: Gray

Technical Details



IP65	-50 C	+105 C
------	-------	--------

Product Code	Size I	A	B	C	D	E	F	Net Weight (kg/m)	In Pack (m)
LD716	1/2"	16.00	21.00	2.50	82.50			0,426	30.50
LD721	3/4"	21.00	26.00	2.50	108.00			0,603	30.50
LD726	1"	26.00	34.00	4.00	165.00				30.50
LD735	1 1/4"	35.00	42.00	3.50	203.00			0,985	15.00
LD740	1 1/2"	40.00	48.00	4.00	228.50				15.00
LD752	2"	52.00	60.00	4.00	282.50				7.50
LD763	2 1/2"	63.00	73.00	5.00	374.50				10.00
LD778	3"	78.00	89.00	5.50	444.50				10.00
LD802	4"	102.00	114.00	6.00	609.50				5.00