




FLEXIBLE CONDUIT, STEEL, LIQUID-TIGHT BLACK UL LISTED

- material : hot-dip galvanized
- standard : UL360
- color : 9005
- Liquid-Tight Flexible conduit of Hot-dipped galvanized steel strip wound with plain PVC oversheath
- Self-extinguishing
- High resistance to abrasion, diluted acids, oils, electrical insulation
- Superior mechanical, abrasion and wear performance
- Size 3/8" through 4" must be installed with a separate ground wire
- Oil-resistant, flame retardant, and sunlight (ultraviolet, UV) resistant
- Compression strength : 1250N
- Impact strength : 6J
- RoHS, REACH and UL 360 compliant PVC jacketed
- UL Listed
- Color: Black

Technical Details



IP65	-50 C	+105 C
------	-------	--------

Product Code	Size I	A	B	C	D	E	F	Net Weight (kg/m)	In Pack (m)
LD013	3/8"	12.50	18.00	2.50	50.50				30.00
LD016	1/2"	16.00	21.00	2.50	82.50				30.00
LD021	3/4"	21.00	26.00	2.50	108.00				30.00
LD026	1"	26.00	34.00	4.00	165.00				20.00
LD035	1 1/4"	35.00	42.00	3.50	203.00				20.00
LD040	1 1/2"	40.00	48.00	4.00	228.50				20.00
LD052	2"	52.00	60.00	4.00	282.50				15.00
LD063	2 1/2"	63.00	73.00	5.00	374.50			2,850	8.00
LD078	3"	78.00	89.00	5.50	444.50				8.00
LD102	4"	102.00	114.00	6.00	609.50				5.00