


## FLEXIBLE STAINLESS CONDUIT, HIGH TEMP, STAINLESS BRAIDED



- material : stainless steel

- Constructed with a stainless steel (SS304) body
- Reinforced with a fiberglass braid and an additional outer SS304 overbraid
- Designed for high temperature resistance, offering excellent protection against sparks and suitable for use in welding environments
- Provides superior durability with high flexibility

### Technical Details



IP43

-40 C

+150 C

| Product Code | Size I | A      | B      | C | D | E | F | Net Weight (kg/m) | In Pack (m) |
|--------------|--------|--------|--------|---|---|---|---|-------------------|-------------|
| SLA008       | 5/16"  | 8.00   | 13.00  |   |   |   |   |                   | 50.00       |
| SLA010       | 1/4"   | 10.00  | 15.00  |   |   |   |   |                   | 50.00       |
| SLA013       | 3/8"   | 12.50  | 18.00  |   |   |   |   | 0,283             | 50.00       |
| SLA016       | 1/2"   | 16.00  | 22.00  |   |   |   |   | 0,321             | 50.00       |
| SLA021       | 3/4"   | 20.50  | 27.00  |   |   |   |   | 0,405             | 50.00       |
| SLA026       | 1"     | 26.50  | 34.00  |   |   |   |   | 0,636             | 40.00       |
| SLA035       | 1 1/4" | 35.00  | 43.00  |   |   |   |   |                   | 30.00       |
| SLA040       | 1 1/2" | 40.00  | 49.00  |   |   |   |   | 1,009             | 30.00       |
| SLA052       | 2"     | 51.50  | 60.00  |   |   |   |   |                   | 20.00       |
| SLA063       | 2 1/2" | 63.00  | 76.00  |   |   |   |   |                   | 10.00       |
| SLA078       | 3"     | 78.00  | 91.00  |   |   |   |   |                   | 10.00       |
| SLA102       | 4"     | 102.00 | 113.00 |   |   |   |   |                   | 5.00        |