

Liquid Tight Non-Metallic Conduit

- UV (sunlight) resistant
- Uses special non-metallic liquid tight connectors for easy installation
- Oil resistant
- UL Listed
- Color: Gray



| | | |
|------|-------|-------|
| IP65 | -25 C | +70 C |
|------|-------|-------|

Technical Details



| Product Code | Size I | A | B | C | D | E | Net Weight (kg/m) | In Pack (m) |
|--------------|--------|-------|-------|------|--------|---|-------------------|-------------|
| GD713 | 3/8" | 12.50 | 18.00 | 2.75 | 51.00 | | | 30.50 |
| GD716 | 1/2" | 16.00 | 21.00 | 2.50 | 72.50 | | | 30.50 |
| GD721 | 3/4" | 21.00 | 26.00 | 2.50 | 108.00 | | | 30.50 |
| GD726 | 1" | 27.00 | 33.00 | 3.00 | 165.00 | | | 30.50 |
| GD735 | 1 1/4" | 35.50 | 42.00 | 3.25 | 203.00 | | | 30.50 |
| GD740 | 1 1/2" | 40.00 | 48.00 | 4.00 | 228.50 | | | 15.25 |
| GD752 | 2" | 52.00 | 60.00 | 4.00 | 282.00 | | | 15.25 |