

Nylon Cable Glands Standard

- Polyamide PA6 core
- CR (Chloroprene) seal
- Flammability: V2 according to UL94
- Best performance for standard industrial applications
- Nylon Cable Glands are great for use in solar power energy systems, electrical equipments and electrical machines
- With T1400 polyamide locknut
- UL Listed
- Color : Black



IP68	-20 C	+100 C
------	-------	--------

Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/pc)	In Pack (pc)
T100203	PG7	3.00	6.00	15.00	8.00		0,005	400.00
T100204	PG9	4.00	8.00	19.00	8.00		0,007	200.00
T100205	PG11	5.00	10.00	22.00	8.00		0,010	100.00
T100206	PG13.5	6.00	12.00	24.00	10.00		0,013	100.00
T100210	PG16	10.00	14.00	27.00	10.00		0,015	100.00
T100213	PG21	13.00	18.00	33.00	11.00		0,027	50.00
T100218	PG29	18.00	25.00	42.00	11.00		0,043	30.00
T100222	PG36	22.00	32.00	53.00	13.00		0,078	12.00
T100230	PG42	30.00	38.00	60.00	13.00		0,103	8.00
T100234	PG48	34.00	44.00	65.00	14.00		0,114	8.00
T100403	M12x1.5	3.00	6.00	15.00	8.00		0,004	300.00
T100404	M16x1.5	4.00	8.00	19.00	8.00		0,007	200.00
T100405	M16x1.5	5.00	10.00	22.00	10.00		0,011	100.00
T100406	M20x1.5	6.00	12.00	24.00	10.00		0,013	100.00
T100410	M20x1.5	10.00	14.00	27.00	10.00		0,016	100.00
T100412	M25x1.5	9.00	13.00	29.00	8.00		0,202	50.00
T100413	M25x1.5	13.00	18.00	33.00	10.00		0,026	60.00

"Your Conduit Partner"

T100418	M32x1.5	18.00	25.00	42.00	15.00		0,043	30.00
T100422	M40x1.5	22.00	32.00	53.00	18.00		0,079	18.00
T100430	M50x1.5	30.00	38.00	60.00	18.00		0,104	10.00
T100434	M63x1.5	34.00	44.00	65.00	18.00		0,124	6.00
T100805	NPT 3/8"	5.00	10.00	22.00	15.00			
T100810	NPT 1/2"	10.00	14.00	27.00	15.00		0,017	80.00
T100813	NPT 3/4"	13.00	18.00	33.00	15.00		0,028	50.00
T100818	NPT 1"	18.00	25.00	42.00	18.00		0,044	20.00