

## LIQUID-TIGHT CONNECTOR METALLIC FEMALE

- Die cast zinc
- Liquid-tight female connector for metallic flexible conduits
- Inside : PA6 Ring and galvanized ferrule
- High corrosion protection
- High vibration and traction resistance



|      |       |       |
|------|-------|-------|
| IP65 | -25 C | +70 C |
|------|-------|-------|

### Technical Details



| Product Code | Size I | A      | B | C | D | E | Net Weight (kg/pc) | In Pack (pc) |
|--------------|--------|--------|---|---|---|---|--------------------|--------------|
| L320613      | 1/2"   | 13.00  |   |   |   |   | 0,035              | 100.00       |
| L320616      | 1/2"   | 16.00  |   |   |   |   | 0,044              | 80.00        |
| L320621      | 3/4"   | 21.00  |   |   |   |   | 0,063              | 50.00        |
| L320626      | 1"     | 26.00  |   |   |   |   | 0,094              | 25.00        |
| L320635      | 1 1/4" | 35.00  |   |   |   |   | 0,139              | 20.00        |
| L320640      | 1 1/2" | 40.00  |   |   |   |   | 0,203              | 12.00        |
| L320652      | 2"     | 52.00  |   |   |   |   | 0,291              | 8.00         |
| L320663      | 2 1/2" | 63.00  |   |   |   |   | 0,661              | 4.00         |
| L320678      | 3"     | 78.00  |   |   |   |   | 0,863              | 3.00         |
| L320702      | 4"     | 102.00 |   |   |   |   |                    |              |