

EX-PROOF CABLE GLAND, STAINLESS STEEL 316L

- Stainless steel 316L core
- For SWA – SWB – STA – PWA – AWA – Shielded cable types
- Without T7400 stainless steel locknut
- ATEX II 2GD Ex db IIC Gb ; Ex eb IIC Gb ; Ex tb IIIC Db, IP66/68



| | | |
|------|-------|--------|
| IP68 | -40 C | +100 C |
|------|-------|--------|

Technical Details



| Product Code | Size I | A | B | C | D | E | Net Weight (kg/pc) | In Pack (pc) |
|--------------|----------|-------|-------|-------|-------|---|--------------------|--------------|
| V710403 | M12x1.5 | 3.00 | 5.50 | 2.00 | 4.00 | | | |
| V710405 | M16x1.5 | 8.50 | 16.00 | 6.00 | 12.00 | | | |
| V710409 | M20x1.5 | 8.50 | 16.00 | 6.00 | 12.00 | | | |
| V710412 | M25x1.5 | 12.00 | 21.00 | 8.50 | 16.00 | | | |
| V710420 | M32x1.5 | 20.00 | 33.00 | 15.00 | 26.00 | | | |
| V710429 | M40x1.5 | 29.00 | 41.00 | 20.00 | 32.00 | | | |
| V710436 | M50x1.5 | 36.00 | 52.00 | 27.00 | 41.00 | | | |
| V710447 | M63x1.5 | 47.00 | 60.00 | 40.00 | 52.00 | | | |
| V710454 | M75x1.5 | 54.00 | 70.00 | 45.00 | 60.00 | | | |
| V710809 | NPT 1/2" | 8.50 | 16.00 | 6.00 | 12.00 | | | |
| V710812 | NPT 3/4" | 12.00 | 21.00 | 8.50 | 16.00 | | | |
| V710820 | NPT 1" | 20.00 | 33.00 | 15.00 | 26.00 | | | |