

EX-PROOF CABLE GLAND, POLYAMIDE




IP68

-40 C

+80 C

Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/pc)	In Pack (pc)
V100203	PG7	3.00	6.50				0,004	300.00
V100204	PG9	4.00	8.00				0,006	200.00
V100205	PG11	5.00	10.00	22.00	8.00		0,009	100.00
V100206	PG13.5	6.00	12.00	24.00	10.00		0,011	100.00
V100210	PG16	10.00	14.00	27.00	10.00		0,013	100.00
V100213	PG21	13.00	18.00	33.00	10.00		0,021	50.00
V100218	PG29	18.00	25.00	42.00	15.00		0,036	30.00
V100222	PG36	22.00	32.00	53.00	18.00		0,068	16.00
V100230	PG42	30.00	38.00	60.00	18.00		0,083	10.00
V100234	PG48	34.00	44.00	65.00	18.00		0,096	8.00
V100404	M12x1.5	4.00	6.00	15.00	10.00		0,004	300.00
V100405	M16x1.5	5.00	8.00	19.00	10.00		0,009	200.00
V100406	M20x1.5	6.00	12.00	24.00	10.00		0,010	100.00
V100410	M20x1.5	10.00	14.00	27.00	10.00		0,013	100.00
V100412	M25x1.5	10.00	14.00	27.00	10.00		0,014	80.00
V100413	M25x1.5	13.00	18.00	33.00	10.00		0,018	60.00
V100418	M32x1.5	18.00	25.00	42.00	15.00		0,039	30.00

V100422	M40x1.5	22.00	32.00	53.00	18.00		0,076	10.00
V100430	M50x1.5	30.00	38.00	60.00	18.00		0,092	10.00
V100434	M63x1.5	34.00	44.00	65.00	18.00		0,100	8.00
V100806	NPT 1/2"	6.00	12.00	24.00	15.00			
V100813	NPT 3/4"	13.00	18.00	33.00	15.00			
V100818	NPT 1"	18.00	25.00	42.00	18.00			