


Infos of VSXFF :



- ☁
- IP67
- MIN
- 20
- MAX
- 80
- CERT
- VSXFF

EX PROOF FLEXIBLE CONDUIT

- ▶ Stainless steel core (AISI316L)
- ▶ Fittings and braiding wire are made of stainless steel AISI304
- ▶ Extremely small bending radius
- ▶ High flexibility
- ▶ Female - Female
- ▶ ATEX
- ▶ II 2G Ex e IIC Gb ; I M2
- ▶ II 2D Ex tb IIIC Db, IP66/67



Sizes & Prices :

Product Code	Size	Size	A (mm)	B (mm)	C (mm)	D (mm)	Meters in Pack (m)	Net Weight (kg/m)
VSX816-0100 FF	NPT 1/2"	NPT 1/2"	16.00	24.00	4.00	1000.00		0,000

Accessories :

EX PROOF FLEXIBLE CONDUIT, MALE MALE



VSXMM

EX PROOF FLEXIBLE CONDUIT

EX-PROOF JUNCTION BOX Exd



V2800

EX-PROOF JUNCTION BOX Exd

EX-PROOF REDUCER, STAINLESS STEEL



V7600

EX-PROOF REDUCER, STAINLESS STEEL

EX-PROOF CONNECTOR, STAINLESS BFF



V7200

EX-PROOF CONNECTOR, STAINLESS BFF