


Infos of VSXMM :



- IP67
- MIN -20
- MAX 80
- CERT
- VSXMM

EX PROOF FLEXIBLE CONDUIT

- ▶ Stainless steel core (AISI316L)
- ▶ Fittings and braiding wire are made of stainless steel AISI304
- ▶ Extremely small bending radius
- ▶ High flexibility
- ▶ Male – Male
- ▶ ATEX
- ▶ II 2G Ex e IIC Gb ; I M2
- ▶ II 2D Ex tb IIIC Db, IP66/67



Sizes & Prices :

Product Code	Size	Size	A (mm)	B (mm)	C (mm)	D (mm)	Meters in Pack (m)	Net Weight (kg/m)
VSX816-0050 MM	NPT 1/2"	NPT 1/2"	16.00	24.00	4.00	500.00		0,000
VSX816-0100 MM	NPT 1/2"	NPT 1/2"	16.00	24.00	4.00	1000.00		0,000
VSX816-0150 MM	NPT 1/2"	NPT 1/2"	16.00	24.00	4.00	1500.00		0,000
VSX816-0200 MM	NPT 1/2"	NPT 1/2"	16.00	24.00	4.00	2000.00		0,000
VSX816-0300 MM	NPT 1/2"	NPT 1/2"	16.00	24.00	4.00	3000.00		0,000
VSX826-0050 MM	NPT 1"	NPT 1"	25.00	35.00	5.00	500.00		0,000

Accessories :

EX PROOF FLEXIBLE CONDUIT, MALE FEMALE



VSXMF

EX PROOF FLEXIBLE CONDUIT

EX-PROOF CONNECTOR, STEEL BFF



V4200

EX-PROOF CONNECTOR, STEEL BFF

EX-PROOF CONNECTOR, STAINLESS BMF



V7000

EX-PROOF CONNECTOR, STAINLESS BMF

EX-PROOF COUPLING, STEEL



V4500

EX-PROOF COUPLING, STEEL