


## EX PROOF FLEXIBLE CONDUIT

- Stainless steel core (AISI316L)
- Fittings and braiding wire are made of stainless steel SS304
- Extremely small bending radius
- High flexibility
- Male - Female
- ATEX
- II 2G Ex e IIC Gb ; I M2
- II 2D Ex tb IIIC Db, IP66/67



IP67	-20 C	+80 C
------	-------	-------

### Technical Details



Product Code	Size I	Size II	A	B	C	D	E	Net Weight (kg/pc)	In Pack (pc)
VSX816-0050MF	NPT 1/2"	NPT 1/2"	12.00	24.00	4.00	500.00		0,209	50.00
VSX816-0075MF	NPT 1/2"	NPT 1/2"	12.00	24.00	4.00	750.00			
VSX816-0100MF	NPT 1/2"	NPT 1/2"	12.00	24.00	4.00	1000.00		0,320	20.00
VSX816-0300MF	NPT 1/2"	NPT 1/2"	12.00	24.00	4.00	3000.00			
VSX816-0400MF	NPT 1/2"	NPT 1/2"	12.00	24.00	4.00	4000.00			
VSX821-0050MF	NPT 3/4"	NPT 3/4"	15.00	22.00	3.50	500.00		0,318	40.00
VSX821-0075MF	NPT 3/4"	NPT 3/4"	15.00	22.00	3.50	750.00		0,431	20.00
VSX821-0100MF	NPT 3/4"	NPT 3/4"	15.00	22.00	3.50	1000.00		0,471	20.00
VSX821-0125MF	NPT 3/4"	NPT 3/4"	15.00	22.00	3.50	1250.00			
VSX821-0150MF	NPT 3/4"	NPT 3/4"	15.00	22.00	3.50	1500.00			
VSX821-0175MF	NPT 3/4"	NPT 3/4"	15.00	22.00	3.50	1750.00			
VSX826-0050MF	NPT 1"	NPT 1"	20.00	30.00	5.00	500.00		0,472	20.00
VSX826-0100MF	NPT 1"	NPT 1"	20.00	30.00	5.00	1000.00		1,000	10.00
VSX835-0050MF	NPT 1 1/4"	NPT 1 1/4"	25.00	35.00	5.00	500.00		0,673	20.00
VSX835-0100MF	NPT 1 1/4"	NPT 1 1/4"	25.00	35.00	5.00	1000.00		0,969	10.00
VSX840-0050MF	NPT 1 1/2"	NPT 1 1/2"	31.00	42.00	5.50	500.00		0,991	15.00
VSX840-0100MF	NPT 1 1/2"	NPT 1 1/2"	31.00	42.00	5.50	1000.00		1,430	12.00

