


EX PROOF FLEXIBLE CONDUIT



- material : stainless steel
- standard : EN60079
- Stainless steel core (AISI316L)
- Fittings and braiding wire are made of stainless steel SS304
- Extremely small bending radius
- High flexibility
- Male - Male
- ATEX
- II 2G Ex e IIC Gb ; I M2
- II 2D Ex tb IIIC Db, IP66/67

Technical Details



IP67

-20 C

+80 C

Product Code	Size I	Size II	A	B	C	D	E	F	Net Weight (kg/pc)	In Pack (pc)
VSX816-0050MM	NPT 1/2"	NPT 1/2"	12.00	18.00	3.00	500.00				
VSX816-0075MM	NPT 1/2"	NPT 1/2"	12.00	18.00	3.00	750.00				
VSX816-0100MM	NPT 1/2"	NPT 1/2"	12.00	18.00	3.00	1000.00			0,320	20.00
VSX816-0150MM	NPT 1/2"	NPT 1/2"	12.00	18.00	3.00	1500.00			0,450	20.00
VSX816-0200MM	NPT 1/2"	NPT 1/2"	12.00	18.00	3.00	2000.00			0,560	20.00
VSX816-0300MM	NPT 1/2"	NPT 1/2"	12.00	18.00	3.00	3000.00				
VSX821-0050MM	NPT 3/4"	NPT 3/4"	15.00	22.00	3.50	500.00				
VSX821-0100MM	NPT 3/4"	NPT 3/4"	15.00	22.00	3.50	1000.00				
VSX821-0150MM	NPT 3/4"	NPT 3/4"	15.00	22.00	3.50	1500.00				
VSX826-0050MM	NPT 1"	NPT 1"	20.00	30.00	5.00	500.00			0,516	30.00
VSX826-0075MM	NPT 1"	NPT 1"	20.00	30.00	5.00	750.00				
VSX826-0100MM	NPT 1"	NPT 1"	20.00	30.00	5.00	1000.00				
VSX863-0050MM	NPT 2 1/2"	NPT 2 1/2"				500.00				