

EX-PROOF LIQUID-TIGHT CONNECTOR, SILOK TYPE

- Brass nickel plated core
- Straight connector for Flexible Conduits
- For non-armoured cables
- Seal Material : Chloroprene
- Without T6400 brass locknut
- ATEX II 2GD Ex db IIC Gb ; Ex eb IIC Gb ; Ex tb IIIC Db, IP66/68




IP68

-40 C

+100 C

Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/pc)	In Pack (pc)
V680410	M20x1.5	10.00	4.00	12.00			0,123	25.00
V680413	M20x1.5	13.00	4.00	10.00				
V680416	M20x1.5	16.00	4.00	12.00			0,103	25.00
V680421	M25x1.5	21.00	10.00	18.00			0,156	25.00
V680426	M32x1.5	26.00	14.00	24.00			0,277	12.00
V680435	M40x1.5	35.00	22.00	32.00			0,463	10.00
V680440	M50x1.5	40.00	26.00	35.00				
V680810	NPT 1/2"	10.00	4.00	12.00			0,129	25.00
V680813	NPT 1/2"	13.00	4.00	10.00				
V680816	NPT 1/2"	16.00	4.00	12.00			0,111	25.00
V680821	NPT 3/4"	21.00	10.00	18.00			0,163	25.00
V680826	NPT 1"	26.00	14.00	24.00				
V680835	NPT 1 1/4"	35.00	22.00	32.00				
V680840	NPT 1 1/2"	40.00	26.00	35.00				