




FLEXIBLE CONDUIT, STEEL, LIQUID-TIGHT BLACK UL LISTED

- Liquid-Tight Flexible conduit of galvanized steel with plain PVC oversheath
- Self-extinguishing
- High resistance to abrasion, diluted acids, oils, electrical insulation
- Superior mechanical, abrasion and wear performance
- Size 3/8" through 4" must be installed with a separate ground wire
- Compression strength : 1250N
- Impact strength : 6J
- UL360 standard
- UL file no : E118165
- Color: Black

| | | |
|------|-------|--------|
| IP65 | -50 C | +105 C |
|------|-------|--------|

Technical Details



| Product Code | Size I | A | B | C | D | E | Net Weight (kg/m) | In Pack (m) |
|--------------|--------|--------|--------|------|--------|---|-------------------|-------------|
| LD013 | 3/8" | 13.00 | 18.00 | 2.50 | 50.50 | | | 30.00 |
| LD016 | 1/2" | 16.00 | 21.00 | 2.50 | 82.50 | | | 30.00 |
| LD021 | 3/4" | 21.00 | 26.00 | 2.50 | 108.00 | | | 30.00 |
| LD026 | 1" | 26.00 | 34.00 | 4.00 | 165.00 | | | 20.00 |
| LD035 | 1 1/4" | 35.00 | 42.00 | 3.50 | 203.00 | | | 20.00 |
| LD040 | 1 1/2" | 40.00 | 48.00 | 4.00 | 228.50 | | | 20.00 |
| LD052 | 2" | 52.00 | 60.00 | 4.00 | 282.50 | | | 15.00 |
| LD063 | 2 1/2" | 63.00 | 73.00 | 5.00 | 374.50 | | | 10.00 |
| LD078 | 3" | 78.00 | 89.00 | 5.50 | 444.50 | | | 10.00 |
| LD102 | 4" | 102.00 | 114.00 | 6.00 | 609.50 | | | 5.00 |