



FLEXIBLE CONDUIT, STEEL, LIQUID-TIGHT BLACK

- Liquid-Tight Flexible conduit of galvanized steel with plain PVC overshath
- Self-extinguishing
- High flexibility
- High resistance to oils, electrical insulation
- Superior mechanical, abrasion and wear performance
- Using L3000 and L6000 fittings the protection degree is IP68
- Compression strength : 1250N
- Impact strength : 6J
- Color: Black

IP65	-10 C	+70 C
------	-------	-------

Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/m)	In Pack (m)
LT010	1/4"	10.00	15.00	2.50	50.00		0,240	50.00
LT013	3/8"	13.00	18.00	2.50	60.00		0,280	50.00
LT016	1/2"	16.00	22.00	3.00	80.00		0,410	50.00
LT021	3/4"	21.00	26.00	2.50	100.00		0,480	30.00
LT026	1"	26.00	34.00	4.00	150.00		0,680	30.00
LT035	1 1/4"	35.00	43.00	4.00	180.00		0,860	20.00
LT040	1 1/2"	40.00	48.00	4.00	220.00		1,080	20.00
LT052	2"	51.00	61.00	5.00	250.00		2,130	15.00
LT063	2 1/2"	63.00	73.00	5.00	300.00		2,610	15.00
LT078	3"	78.00	89.00	5.50	450.00		3,210	10.00
LT102	4"	102.00	114.00	6.00	600.00		4,550	10.00