




## FLEXIBLE CONDUIT, LIQUID-TIGHT STAINLESS BRAIDED

- Liquid-Tight Flexible conduit of galvanized steel with plain PVC overshath
- Outside stainless steel (SS304) wire braided
- Used in the presence of sparks welding slay, die casting machines burnes and similar applications
- Provides EMC screening
- High flexibility
- Waterproof and high tension resistant

|      |       |       |
|------|-------|-------|
| IP65 | -20 C | +70 C |
|------|-------|-------|

### Technical Details



| Product Code | Size I | A      | B      | C    | D | E | Net Weight (kg/m) | In Pack (m) |
|--------------|--------|--------|--------|------|---|---|-------------------|-------------|
| LTX010       | 1/4"   | 10.00  | 16.00  | 3.00 |   |   |                   | 50.00       |
| LTX013       | 3/8"   | 13.00  | 19.00  | 3.00 |   |   |                   | 50.00       |
| LTX016       | 1/2"   | 16.00  | 23.00  | 3.50 |   |   |                   | 50.00       |
| LTX021       | 3/4"   | 21.00  | 28.00  | 3.50 |   |   |                   | 30.00       |
| LTX026       | 1"     | 26.00  | 36.00  | 5.00 |   |   |                   | 30.00       |
| LTX035       | 1 1/4" | 35.00  | 45.00  | 5.00 |   |   |                   | 20.00       |
| LTX040       | 1 1/2" | 40.00  | 50.00  | 5.00 |   |   |                   | 20.00       |
| LTX052       | 2"     | 51.00  | 63.00  | 6.00 |   |   |                   | 15.00       |
| LTX063       | 2 1/2" | 63.00  | 75.00  | 6.00 |   |   |                   | 10.00       |
| LTX078       | 3"     | 78.00  | 91.00  | 6.50 |   |   |                   | 10.00       |
| LTX102       | 4"     | 102.00 | 116.00 | 7.00 |   |   |                   | 10.00       |