



## FLEXIBLE CONDUIT, LIQUID-TIGHT UV RESISTANT


- Liquid-Tight Flexible conduit of galvanized steel with rubber oversheath
- RoHS, REACH and UL 360 compliant PVC jacketed
- Inner core made from a spiral wound strip of corrosion resistant galvanized steel
- Resistance to Wide Temperature Range exposure
- Durable and long life
- High resistance to oils, electrical insulation
- Superior mechanical, abrasion and wear performance
- Compression strength : 1250N
- Impact strength : 6J
- Using L3000 and L6000 fittings the protection degree is IP68
- Color: Black

IP67

-55 C

+105 C

### Technical Details



| Product Code | Size I | A      | B      | C    | D      | E | Net Weight (kg/m) | In Pack (m) |
|--------------|--------|--------|--------|------|--------|---|-------------------|-------------|
| LTR010       | 1/4"   | 10.00  | 15.00  | 2.50 | 50.00  |   |                   | 50.00       |
| LTR013       | 3/8"   | 13.00  | 18.00  | 2.50 | 60.00  |   |                   | 50.00       |
| LTR016       | 1/2"   | 16.00  | 22.00  | 3.00 | 80.00  |   |                   | 50.00       |
| LTR021       | 3/4"   | 21.00  | 26.00  | 2.50 | 100.00 |   |                   | 30.00       |
| LTR026       | 1"     | 26.00  | 34.00  | 4.00 | 150.00 |   |                   | 20.00       |
| LTR035       | 1 1/4" | 35.00  | 43.00  | 4.00 | 180.00 |   |                   | 15.00       |
| LTR040       | 1 1/2" | 40.00  | 48.00  | 4.00 | 200.00 |   |                   | 15.00       |
| LTR052       | 2"     | 52.00  | 61.00  | 4.50 | 250.00 |   |                   | 10.00       |
| LTR063       | 2 1/2" | 63.00  | 73.00  | 5.00 | 375.00 |   |                   | 8.00        |
| LTR078       | 3"     | 78.00  | 89.00  | 5.50 | 445.00 |   |                   | 8.00        |
| LTR102       | 4"     | 102.00 | 114.00 | 6.00 | 610.00 |   |                   | 5.00        |