




## FLEXIBLE CONDUIT, STAINLESS STEEL

- material : stainless steel
- standard : EN61386
- Stainless steel core (SS304)
- Extremely small bending radius
- High flexibility
- Non liquid – tight

### Technical Details



|      |       |        |
|------|-------|--------|
| IP42 | -40 C | +350 C |
|------|-------|--------|

| Product Code | Size I | A      | B      | C    | D      | E | F | Net Weight (kg/m) | In Pack (m) |
|--------------|--------|--------|--------|------|--------|---|---|-------------------|-------------|
| SL010        | 1/4"   | 10.00  | 13.50  | 1.75 | 25.00  |   |   | 0,075             | 100.00      |
| SL013        | 3/8"   | 12.50  | 16.00  | 1.75 | 33.00  |   |   | 0,113             | 50.00       |
| SL016        | 1/2"   | 16.00  | 19.50  | 1.75 | 38.00  |   |   | 0,156             | 50.00       |
| SL021        | 3/4"   | 20.50  | 25.00  | 2.25 | 45.00  |   |   | 0,204             | 50.00       |
| SL026        | 1"     | 26.50  | 30.50  | 2.25 | 55.00  |   |   | 0,251             | 50.00       |
| SL035        | 1 1/4" | 35.00  | 40.00  | 2.50 | 62.00  |   |   | 0,395             | 30.00       |
| SL040        | 1 1/2" | 40.00  | 45.00  | 2.50 | 90.00  |   |   | 0,408             | 30.00       |
| SL052        | 2"     | 51.50  | 56.50  | 2.50 | 110.00 |   |   | 0,637             | 20.00       |
| SL063        | 2 1/2" | 63.00  | 70.50  | 3.75 | 130.00 |   |   | 1,025             | 10.00       |
| SL078        | 3"     | 78.00  | 85.50  | 3.75 | 160.00 |   |   | 1,238             | 10.00       |
| SL102        | 4"     | 102.00 | 109.00 | 3.75 | 210.00 |   |   | 1,736             | 5.00        |