




FLEXIBLE STEEL CONDUIT HALOGEN-FREE COATED, BLACK

- Flexible conduit of galvanized steel with Halogen-free oversheath
- Using L3000 and L6000 fittings the protection degree is IP66
- Color : Black

| | | |
|------|-------|-------|
| IP57 | -10 C | +70 C |
|------|-------|-------|

Technical Details



| Product Code | Size I | A | B | C | D | E | Net Weight (kg/m) | In Pack (m) |
|--------------|--------|--------|--------|------|---|---|-------------------|-------------|
| BFH008 | | 8.00 | 11.00 | | | | | |
| BFH010 | 1/4" | 10.00 | 13.00 | | | | 0,108 | 50.00 |
| BFH013 | 3/8" | 13.00 | 16.00 | | | | 0,110 | 50.00 |
| BFH016 | 1/2" | 16.00 | 19.00 | | | | 0,122 | 50.00 |
| BFH018 | | 18.00 | 21.00 | | | | | 50.00 |
| BFH021 | 3/4" | 21.00 | 25.00 | | | | 0,189 | 50.00 |
| BFH026 | 1" | 26.00 | 30.00 | | | | 0,208 | 25.00 |
| BFH035 | 1 1/4" | 35.00 | 39.00 | | | | 0,288 | 25.00 |
| BFH040 | 1 1/2" | 40.00 | 44.00 | | | | 0,505 | 25.00 |
| BFH052 | 2" | 52.00 | 57.00 | | | | 0,565 | 25.00 |
| BFH063 | 2 1/2" | 63.00 | 71.00 | 4.00 | | | | 25.00 |
| BFH078 | 3" | 78.00 | 87.00 | 4.50 | | | 0,837 | 15.00 |
| BFH102 | 4" | 102.00 | 110.00 | 4.50 | | | | 10.00 |