


FLEXIBLE STEEL CONDUIT PVC COATED, BLACK

- Flexible conduit of galvanized steel with PVC oversheath
- Sheet thickness : 0,18mm
- Compression strength : 320N
- Impact strength : 1J
- Using L3000 and L6000 fittings the protection degree is IP66
- Color : Black



IP57	-10 C	+70 C
------	-------	-------

Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/m)	In Pack (m)
BF010	1/4"	10.00	13.00	1.50			0,086	50.00
BF011		11.00	14.00	1.50			0,089	50.00
BF013	3/8"	13.00	16.00	1.50			0,105	50.00
BF014		14.00	17.00	1.50				50.00
BF016	1/2"	16.00	19.00	1.50			0,124	50.00
BF018		18.00	21.00	1.50				50.00
BF021	3/4"	21.00	25.00	2.00			0,161	50.00
BF026	1"	26.00	30.00	2.00			0,216	25.00
BF029		29.00	33.00	2.00				25.00
BF035	1 1/4"	35.00	40.00	2.50			0,288	25.00
BF040	1 1/2"	40.00	45.00	2.50			0,505	25.00
BF052	2"	50.00	55.00	2.50			0,565	25.00
BF063	2 1/2"	62.50	67.50	2.50			0,682	25.00
BF078	3"	78.00	87.00	4.50			0,837	15.00
BF102	4"	102.00	110.00	4.50			1,641	10.00