




FLEXIBLE STEEL CONDUIT PVC COATED, GRAY

- material : electro galvanized
- Flexible conduit of galvanized steel with PVC oversheath
- Sheet thickness : 0,18mm
- Compression strength : 320N
- Impact strength : 1J
- Using L3000 and L6000 fittings the protection degree is IP66
- Color : Gray

Technical Details



IP57	-10 C	+70 C
------	-------	-------

Product Code	Size I	A	B	C	D	E	F	Net Weight (kg/m)	In Pack (m)
BF710	1/4"	10.00	13.00	1.50				0,086	50.00
BF711		11.00	14.00	1.50				0,089	50.00
BF713	3/8"	12.50	16.00	1.75				0,105	50.00
BF714		14.00	17.50	1.75					50.00
BF716	1/2"	16.00	19.50	1.75				0,126	50.00
BF718		18.00	21.50	1.75				0,131	50.00
BF721	3/4"	21.00	25.00	2.00				0,151	50.00
BF726	1"	26.00	30.00	2.00				0,216	25.00
BF735	1 1/4"	35.00	39.00	2.00				0,288	25.00
BF740	1 1/2"	40.00	44.00	2.00				0,505	25.00
BF752	2"	50.00	55.00	2.50				0,565	25.00
BF763	2 1/2"	62.50	67.50	2.50				0,682	25.00