


Infos of BS700 :



IP57
MIN
-15
MAX
70
CERT
BS700

FLEXIBLE STEEL CONDUIT PVC COATED GRAY

- ▶ Flexible conduit of galvanized steel with plain PVC oversheath
- ▶ Sheet thickness : 0,25mm
- ▶ Compression strength : 750N
- ▶ Impact strength : 2J
- ▶ The PVC oversheath has high resistance to abrasion, diluted acids, oils
- ▶ Resistance to weathering
- ▶ Using L3000 fittings the protection degree is IP66
- ▶ Color : Gray



Sizes & Prices :

Product Code	Size	Size	A (mm)	B (mm)	C (mm)	D (mm)	Meters in Pack (m)	Net Weight (kg/m)
BS710	1/4"		10.00	14.50	2.25	50.00	100.00	0,101
BS713	3/8"		13.00	18.00	2.50	50.00	50.00	0,124
BS716	1/2"		16.00	21.00	2.50	65.00	50.00	0,201
BS721	3/4"		21.00	26.00	2.50	75.00	50.00	0,275
BS726	1"		26.00	32.00	3.00	100.00	50.00	0,467
BS735	1 1/4"		35.00	41.00	3.00	125.00	30.00	0,682
BS740	1 1/2"		40.00	47.00	3.50	150.00	30.00	0,751
BS752	2"		51.00	59.00	4.00	175.00	20.00	1,017
BS763	2 1/2"		63.00	73.00	5.00	200.00	10.00	1,871
BS778	3"		78.00	89.00	5.50	225.00	10.00	2,051
BS802	4"		102.00	114.00	6.00	275.00	10.00	2,285

Accessories :

SCREW-IN COUPLING FOR METALLIC CONDUIT



B3560

Flexible Metallic Conduit to Flexible Metallic Conduit

FERRULE, METALLIC



B3700

FERRULE, METALLIC

FLEXIBLE STEEL CONDUIT PVC COATED GRAY



BS700

FLEXIBLE STEEL CONDUIT PVC COATED GRAY

FLEXIBLE STEEL CONDUIT PVC COATED, GRAY



BF700

FLEXIBLE STEEL CONDUIT PVC COATED, GRAY