

### FLEXIBLE STEEL CONDUIT STAINLESS BRAIDED



- Flexible conduit of galvanized steel with plain PVC oversheath
- Outside stainless steel wire braided
- Used in the presence of sparks welding slay, die casting machines burnes and similar applications
- Self-extinguishing
- Provides EMC screening
- High flexibility
- Waterproof and high tension resistant
- Using L3000 fittings the protection degree is IP66

IP43	-15 C	+70 C
------	-------	-------

#### Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/m)	In Pack (m)
BSXS008	5/16"	8.00	13.00					100.00
BSXS010	1/4"	10.00	15.00				0,188	50.00
BSXS013	3/8"	13.00	18.00				0,288	50.00
BSXS016	1/2"	16.00	22.00				0,402	50.00
BSXS021	3/4"	21.00	29.00				0,537	50.00
BSXS026	1"	26.00	32.00				0,545	25.00
BSXS035	1 1/4"	35.00	43.00					25.00
BSXS040	1 1/2"	40.00	50.00					25.00
BSXS052	2"	52.00	63.00					20.00
BSXS063	2 1/2"	63.00	79.00					10.00
BSXS078	3"	78.00	94.00					10.00
BSXS102	4"	102.00	118.00					5.00