

FLEXIBLE CONDUIT, LIQUID-TIGHT STAINLESS BRAIDED

- Liquid-Tight Flexible conduit of galvanized steel with plain PVC overseath
- Outside stainless steel (SS304) wire braided
- Used in the presence of sparks welding slay, die casting machines burnes and similar applications
- Provides EMC screening
- High flexibility
- Waterproof and high tension resistant



IP65	-20 C	+70 C
------	-------	-------

Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/m)	In Pack (m)
LTX010	1/4"	10.00	16.00	3.00				50.00
LTX013	3/8"	13.00	19.00	3.00				50.00
LTX016	1/2"	16.00	23.00	3.50				50.00
LTX021	3/4"	21.00	28.00	3.50				30.00
LTX026	1"	26.00	36.00	5.00				30.00
LTX035	1 1/4"	35.00	45.00	5.00				20.00
LTX040	1 1/2"	40.00	50.00	5.00				20.00
LTX052	2"	51.00	63.00	6.00				15.00
LTX063	2 1/2"	63.00	75.00	6.00				10.00
LTX078	3"	78.00	91.00	6.50				10.00
LTX102	4"	102.00	116.00	7.00				10.00