



## FLEXIBLE CONDUIT, LIQUID-TIGHT UV RESISTANT

- Liquid-Tight Flexible conduit of galvanized steel with rubber oversheath
- RoHS, REACH and UL 360 compliant PVC jacketed
- Inner core made from a spiral wound strip of corrosion resistant galvanized steel
- Resistance to Wide Temperature Range exposure
- Durable and long life
- High resistance to oils, electrical insulation
- Superior mechanical, abrasion and wear performance
- Compression strength : 1250N
- Impact strength : 6J
- Using L3000 and L6000 fittings the protection degree is IP68
- Color: Black

IP67	-55 C	+105 C
------	-------	--------

### Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/m)	In Pack (m)
LTR010	1/4"	10.00	15.00	2.50	50.00			50.00
LTR013	3/8"	13.00	18.00	2.50	60.00			50.00
LTR016	1/2"	16.00	22.00	3.00	80.00			50.00
LTR021	3/4"	21.00	26.00	2.50	100.00			30.00
LTR026	1"	26.00	34.00	4.00	150.00			20.00
LTR035	1 1/4"	35.00	43.00	4.00	180.00			15.00
LTR040	1 1/2"	40.00	48.00	4.00	200.00			15.00
LTR052	2"	52.00	61.00	4.50	250.00			10.00
LTR063	2 1/2"	63.00	73.00	5.00	375.00			8.00
LTR078	3"	78.00	89.00	5.50	445.00			8.00
LTR102	4"	102.00	114.00	6.00	610.00			5.00