



FLEXIBLE CONDUIT, STEEL, LIQUID-TIGHT BLACK UL LISTED


- Liquid-Tight Flexible conduit of galvanized steel with plain PVC oversheath
- Self-extinguishing
- High resistance to abrasion, diluted acids, oils, electrical insulation
- Superior mechanical, abrasion and wear performance
- Size 3/8" through 4" must be installed with a separate ground wire
- Compression strength : 1250N
- Impact strength : 6J
- UL360 standard
- UL file no : E118165
- Color: Black

IP65

-50 C

+105 C

Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/m)	In Pack (m)
LD013	3/8"	13.00	18.00	2.50	50.50			30.00
LD016	1/2"	16.00	21.00	2.50	82.50			30.00
LD021	3/4"	21.00	26.00	2.50	108.00			30.00
LD026	1"	26.00	34.00	4.00	165.00			20.00
LD035	1 1/4"	35.00	42.00	3.50	203.00			20.00
LD040	1 1/2"	40.00	48.00	4.00	228.50			20.00
LD052	2"	52.00	60.00	4.00	282.50			15.00
LD063	2 1/2"	63.00	73.00	5.00	374.50			10.00
LD078	3"	78.00	89.00	5.50	444.50			10.00
LD102	4"	102.00	114.00	6.00	609.50			5.00