


## IMC CONDUIT HDG

- Hot-dip galvanized steel core
- Electromagnetic interference screen system
- Easy carry and montage
- Mechanical protection
- IMC interior coating provides a smooth surface for faster wire pulling
- High grade durable & ductile steel for long life
- IMC is manufactured 10-foot (3,05 meters) lengths
- UL Listed
- With galvanized sleeve (one piece)



### Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/m)	In Pack (m)
NS016	1/2"	16.76	20.70	1.97			0,920	30.50
NS021	3/4"	21.93	26.13	2.10			1,250	30.50
NS026	1"	28.07	32.76	2.35			1,770	30.50
NS035	1 1/4"	36.75	41.60	2.42			2,350	9.15
NS040	1 1/2"	42.74	47.82	2.54			2,890	9.15
NS052	2"	54.59	59.94	2.67			3,810	6.10
NS063	2 1/2"	64.90	72.52	3.81			5,560	3.05
NS078	3"	80.67	88.29	3.81			6,710	3.05
NS090	3 1/2"	93.24	100.86	3.81			9,350	3.05
NS102	4"	105.82	113.44	3.81			10,410	3.05
NS125	5"							3.05
NS150	6"							3.05