




FLEXIBLE CONDUIT, STEEL, LFMC

- material : hot-dip galvanized
- standard : ROHS UL360
- color : 9005
- Liquid-Tight Flexible conduit of galvanized steel with plain PVC oversheath
- Self-extinguishing
- High flexibility
- High resistance to oils, electrical insulation
- Superior mechanical, abrasion and wear performance
- Using L3000 and L6000 fittings the protection degree is IP68
- Compression strength : 1250N
- Impact strength : 6J
- RoHS, REACH and UL 360 compliant PVC jacketed
- Color: Black

Technical Details



IP65	-10 C	+70 C
------	-------	-------

Product Code	Size I	A	B	C	D	E	F	Net Weight (kg/m)	In Pack (m)
LT010	1/4"	10.00	15.00	2.50	50.00			0,240	50.00
LT013	3/8"	12.50	18.00	2.75	60.00			0,280	50.00
LT016	1/2"	16.00	21.00	2.50	80.00			0,329	50.00
LT021	3/4"	21.00	26.00	2.50	100.00			0,428	30.00
LT026	1"	26.50	33.00	3.25	150.00			0,583	30.00
LT035	1 1/4"	35.00	42.00	3.50	180.00			0,860	20.00
LT040	1 1/2"	40.00	48.00	4.00	220.00			1,080	20.00
LT052	2"	52.00	60.00	4.00	250.00			2,130	15.00
LT063	2 1/2"	63.00	73.00	5.00	300.00			2,610	15.00
LT078	3"	78.00	89.00	5.50	450.00			3,210	10.00
LT102	4"	102.00	114.00	6.00	600.00			4,550	10.00