




## FLEXIBLE CONDUIT, STEEL, LFMC

- material : hot-dip galvanized
- standard : ROHS UL360
- Liquid-Tight Flexible conduit of galvanized steel with plain PVC overshath
- Self-extinguishing
- High flexibility
- High resistance to oils, electrical insulation
- Superior mechanical, abrasion and wear performance
- Using L3000 and L6000 fittings the protection degree is IP68
- Compression strength : 1250N
- Impact strength : 6J
- RoHS, REACH and UL 360 compliant PVC jacketed
- Color: Gray

### Technical Details



IP65	-10 C	+70 C
------	-------	-------

Product Code	Size I	A	B	C	D	E	F	Net Weight (kg/m)	In Pack (m)
LT710	1/4"	10.00	15.00	2.50	50.00			0,240	50.00
LT713	3/8"	12.50	18.00	2.75	60.00			0,280	30.00
LT716	1/2"	16.00	21.00	2.50	80.00			0,410	50.00
LT721	3/4"	21.00	26.00	2.50	100.00			0,480	30.00
LT726	1"	26.50	33.00	3.25	150.00			0,680	30.00
LT735	1 1/4"	35.00	42.00	3.50	180.00			0,860	15.00
LT740	1 1/2"	40.00	48.00	4.00	220.00			1,080	15.00
LT752	2"	52.00	60.00	4.00	250.00			2,130	15.00
LT763	2 1/2"	63.00	73.00	5.00	300.00			2,610	15.00
LT778	3"	78.00	89.00	5.50	450.00			3,210	15.00
LT802	4"	102.00	114.00	6.00	600.00			4,550	10.00