




## FLEXIBLE CONDUIT, STAINLESS STEEL, SMALL-BORE

- Stainless steel core (SS304)
- Extremely small bending radius
- High flexibility
- Non liquid - tight

|      |       |        |
|------|-------|--------|
| IP42 | -40 C | +350 C |
|------|-------|--------|

### Technical Details



| Product Code | Size I | A     | B     | C    | D | E | Net Weight (kg/m) | In Pack (m) |
|--------------|--------|-------|-------|------|---|---|-------------------|-------------|
| SS04         |        | 4.50  | 6.50  | 1.00 |   |   | 0,035             | 100.00      |
| SS05         |        | 4.80  | 6.80  | 1.00 |   |   | 0,046             | 200.00      |
| SS06         |        | 6.40  | 8.40  | 1.00 |   |   | 0,061             | 100.00      |
| SS07         |        | 7.20  | 9.50  | 1.15 |   |   | 0,072             | 50.00       |
| SS08         |        | 8.00  | 10.90 | 1.45 |   |   | 0,081             | 50.00       |
| SS09         |        | 9.00  | 11.20 | 2.20 |   |   |                   |             |
| SS10         |        | 9.50  | 12.70 | 1.60 |   |   | 0,078             | 100.00      |
| SS13         |        | 12.70 | 15.00 |      |   |   | 0,157             | 50.00       |