


## FLEXIBLE STAINLESS CONDUIT, HIGH TEMP, STAINLESS BRAIDED



- material : stainless steel
- Constructed with a stainless steel (SS304) body
- Reinforced with a fiberglass braid and an additional outer SS304 overbraid
- Designed for high temperature resistance, offering excellent protection against sparks and suitable for use in welding environments
- Provides superior durability with high flexibility

### Technical Details



IP43	-40 C	+150 C
------	-------	--------

Product Code	Size I	A	B	C	D	E	F	Net Weight (kg/m)	In Pack (m)
SLA008	5/16"	8.00	13.00						50.00
SLA010	1/4"	10.00	15.00						50.00
SLA013	3/8"	12.50	18.00					0,283	50.00
SLA016	1/2"	16.00	22.00					0,321	50.00
SLA021	3/4"	20.50	27.00					0,405	50.00
SLA026	1"	26.50	34.00					0,636	40.00
SLA035	1 1/4"	35.00	43.00						30.00
SLA040	1 1/2"	40.00	49.00					1,009	30.00
SLA052	2"	51.50	60.00						20.00
SLA063	2 1/2"	63.00	76.00						10.00
SLA078	3"	78.00	91.00						10.00
SLA102	4"	102.00	113.00						5.00