


Nylon Cable Glands Standard

- Polyamide PA6 core
- CR (Chloroprene) seal
- Flammability: V2 according to UL94
- Best performance for standard industrial applications
- Nylon Cable Glands are great for use in solar power energy systems, electrical equipments and electrical machines
- With T1470 polyamide locknut
- UL Listed
- Color : Gray



IP68	-20 C	+100 C
------	-------	--------

Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/pc)	In Pack (pc)
T107203	PG7	3.00	6.00	15.00	8.00		0,005	400.00
T107204	PG9	4.00	8.00	19.00	8.00		0,007	200.00
T107205	PG11	5.00	10.00	22.00	8.00		0,010	100.00
T107206	PG13.5	6.00	12.00	24.00	10.00		0,013	100.00
T107210	PG16	10.00	14.00	27.00	10.00		0,015	100.00
T107213	PG21	13.00	18.00	33.00	11.00		0,027	50.00
T107218	PG29	18.00	25.00	42.00	11.00		0,043	30.00
T107222	PG36	22.00	32.00	53.00	13.00		0,078	12.00
T107230	PG42	30.00	38.00	60.00	13.00		0,103	8.00
T107234	PG48	34.00	44.00	65.00	14.00		0,114	8.00
T107403	M12x1.5	3.00	6.00	15.00	8.00		0,004	300.00
T107404	M16x1.5	4.00	8.00	19.00	8.00		0,007	200.00
T107405	M16x1.5	5.00	10.00	22.00	10.00		0,011	100.00
T107406	M20x1.5	6.00	12.00	24.00	10.00		0,013	100.00
T107410	M20x1.5	10.00	14.00	27.00	10.00		0,016	100.00
T107413	M25x1.5	13.00	18.00	33.00	10.00		0,026	60.00
T107418	M32x1.5	18.00	25.00	42.00	15.00		0,043	30.00

"Your Conduit Partner"

T107421	M40x1.5	19.00	28.00	46.00	10.00			
T107422	M40x1.5	22.00	32.00	53.00	18.00		0,079	18.00
T107430	M50x1.5	30.00	38.00	60.00	18.00		0,104	10.00
T107434	M63x1.5	34.00	44.00	65.00	18.00		0,124	6.00
T107805	NPT 3/8"	5.00	10.00	22.00	15.00			
T107810	NPT 1/2"	10.00	14.00	27.00	15.00		0,017	80.00
T107813	NPT 3/4"	13.00	18.00	33.00	15.00		0,028	50.00
T107818	NPT 1"	18.00	25.00	42.00	18.00		0,044	20.00