

POLYAMIDE CORRUGATED CONDUIT SPLIT, BLACK

- Polyamide PA6 material
- Polyamide annular corrugated flexible conduit, light, it is extremely flexible with a very low bending radius
- Resistant to ageing and weathering good oils and acids
- Halogen-free
- Self Extinguishing flame retardant UL94 V2-HB
- Split Type
- Color : Black



IP40	-40 C	+120 C
------	-------	--------

Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/m)	In Pack (m)
FNS005		5.00	8.00	1.50	20.00		0,010	100.00
FNS007	PG7	6.50	10.00	1.75	20.00		0,016	100.00
FNS009		8.50	12.00	1.75	20.00		0,025	100.00
FNS010	PG9	10.00	13.00	1.50	25.00		0,025	100.00
FNS012	PG11	12.00	16.00	2.00	30.00		0,036	50.00
FNS014	PG13.5	14.00	19.00	2.50	35.00		0,048	50.00
FNS017	PG16	16.90	21.20	2.15	40.00		0,063	50.00
FNS019		19.50	24.00	2.75	45.00			50.00
FNS023	PG21	23.00	29.00	3.00	50.00		0,090	50.00
FNS026		26.00	31.00	2.50	55.00		0,102	25.00
FNS029	PG29	29.00	34.50	2.75	60.00		0,125	25.00
FNS036	PG36	36.00	43.00	3.50	70.00		0,140	25.00
FNS048	PG48	48.00	54.50	3.25	80.00		0,204	25.00