




The black polyamide (PA6) corrugated conduit is a durable and versatile solution for cable protection in both indoor and outdoor applications. With excellent UV resistance, it ensures long-term reliability under sunlight exposure.

- material : nylon 6
- standard : EN50086
- color : 9005
- Flexible structure for easy cable management and installation
- UV resistant, ideal for outdoor use
- Free from halogen, phosphorous, and cadmium
- Self-extinguishing design compliant with UL94 V2-HB standard
- IP65 dust and water resistance; can reach IP68 with sealing rings
- Resistant to chemicals such as alcohols, grease, mineral oils, kerosene, detergents, and solvents
- Provides reliable, long-lasting performance in harsh environments
- Color : Black

Technical Details



IP65	-40 C	+120 C
------	-------	--------

Product Code	Size I	A	B	C	D	E	F	Net Weight (kg/m)	In Pack (m)
FN005		5.00	7.00	1.00	20.00			0,010	100.00
FN007	PG7	6.50	10.00	1.75	20.00			0,016	100.00
FN009		8.50	12.00	1.75	20.00			0,025	100.00
FN010	PG9	10.00	13.00	1.50	25.00			0,025	100.00
FN012	PG11	12.00	16.00	2.00	30.00			0,036	50.00
FN014	PG13.5	14.00	19.00	2.50	35.00			0,048	50.00
FN017	PG16	16.90	21.20	2.15	40.00			0,059	50.00
FN019		19.50	24.00	2.75	45.00			0,063	50.00
FN023	PG21	23.00	29.00	3.00	50.00			0,090	50.00
FN026		26.00	31.00	2.50	55.00			0,102	25.00
FN029	PG29	29.00	34.50	2.75	60.00			0,125	25.00
FN036	PG36	36.00	43.00	3.50	70.00			0,140	25.00
FN048	PG48	48.00	54.50	3.25	80.00			0,204	25.00