




The grey polyamide (PA6) corrugated conduit is specially designed for machinery and equipment manufacturing, providing insulation, mechanical protection, and organized cable routing. Its high flexibility allows easy installation even in tight spaces.

- material : nylon 6
- standard : EN50086
- color : 7031
- Ideal for machinery, industrial equipment, and automation systems
- Excellent flexibility for easy installation
- Free from halogen, phosphorous, and cadmium
- Self-extinguishing design compliant with UL94 V2-HB standard
- IP65 protection against dust and water; can be upgraded to IP68 with sealing rings
- High resistance to alcohols, grease, mineral oils, kerosene, detergents, and solvents
- Ensures long-lasting and reliable cable protection
- Color : Gray

Technical Details



IP65	-40 C	+120 C
------	-------	--------

Product Code	Size I	A	B	C	D	E	F	Net Weight (kg/m)	In Pack (m)
FN705		5.00	7.00	1.00	20.00			0,010	100.00
FN707	PG7	6.50	10.00	1.75	20.00			0,016	100.00
FN709		8.50	12.00	1.75	20.00			0,025	100.00
FN710	PG9	10.00	13.00	1.50	25.00			0,025	100.00
FN712	PG11	12.00	16.00	2.00	30.00			0,032	50.00
FN714	PG13.5	14.00	19.00	2.50	35.00			0,048	50.00
FN717	PG16	17.00	21.00	2.00	40.00			0,059	50.00
FN719		19.50	24.00	2.75	45.00			0,063	50.00
FN723	PG21	23.00	29.00	3.00	50.00			0,090	50.00
FN726		26.00	31.00	2.50	55.00			0,102	25.00
FN729	PG29	29.00	34.50	2.75	60.00			0,125	25.00
FN736	PG36	36.00	43.00	3.50	70.00			0,140	25.00
FN748	PG48	48.00	54.50	3.25	80.00			0,204	25.00