



## POLYAMIDE CONDUIT, FLAME RETARDANT V0, BLACK


- Polyamide PA6 material
- High flexibility
- Polyamide annular corrugated flexible conduit, light, it is extremely flexible with a very low bending radius
- Resistant to ageing and weathering good oils and acids
- Halogen-free
- UV-resistant
- Self Extinguishing flame retardant UL94 V0
- Color : Black

IP55

-40 C

+120 C

### Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/m)	In Pack (m)
FNH005		5.00	8.00	1.50	20.00			100.00
FNH007	PG7	6.50	10.00	1.75	20.00		0,022	100.00
FNH009		8.50	12.00	1.75	20.00		0,025	100.00
FNH010	PG9	10.00	13.00	1.50	25.00		0,026	100.00
FNH012	PG11	12.00	16.00	2.00	30.00		0,034	50.00
FNH014	PG13.5	14.00	19.00	2.50	35.00		0,053	50.00
FNH017	PG16	16.90	21.20	2.15	40.00		0,058	50.00
FNH019		19.50	24.00	2.75	45.00			50.00
FNH023	PG21	23.00	29.00	3.00	50.00		0,090	50.00
FNH026		26.00	31.00	2.50	55.00		0,102	25.00
FNH029	PG29	29.00	34.50	2.75	60.00		0,125	25.00
FNH036	PG36	36.00	43.00	3.50	70.00		0,140	25.00
FNH048	PG48	48.00	54.50	3.25	80.00		0,204	25.00