




POLYAMIDE CORRUGATED CONDUIT, BLACK

- Polyamide PA6 material
- Polyamide annular corrugated flexible conduit, light, it is extremely flexible with a very low bending radius
- Resistant to ageing and weathering good oils and acids
- Halogen-free
- Self Extinguishing flame retardant UL94 V2-HB
- Color : Black

| | | |
|------|-------|--------|
| IP55 | -40 C | +120 C |
|------|-------|--------|

Technical Details



| Product Code | Size I | A | B | C | D | E | Net Weight (kg/m) | In Pack (m) |
|--------------|--------|-------|-------|------|-------|---|-------------------|-------------|
| FN005 | | 5.00 | 8.00 | 1.50 | 20.00 | | 0,010 | 100.00 |
| FN007 | PG7 | 6.50 | 10.00 | 1.75 | 20.00 | | 0,016 | 100.00 |
| FN009 | | 8.50 | 12.00 | 1.75 | 20.00 | | 0,025 | 100.00 |
| FN010 | PG9 | 10.00 | 13.00 | 1.50 | 25.00 | | 0,025 | 100.00 |
| FN012 | PG11 | 12.00 | 16.00 | 2.00 | 30.00 | | 0,036 | 50.00 |
| FN014 | PG13.5 | 14.00 | 19.00 | 2.50 | 35.00 | | 0,048 | 50.00 |
| FN017 | PG16 | 16.90 | 21.20 | 2.15 | 40.00 | | 0,063 | 50.00 |
| FN019 | | 19.50 | 24.00 | 2.75 | 45.00 | | | 50.00 |
| FN023 | PG21 | 23.00 | 29.00 | 3.00 | 50.00 | | 0,090 | 50.00 |
| FN026 | | 26.00 | 31.00 | 2.50 | 55.00 | | 0,102 | 25.00 |
| FN029 | PG29 | 29.00 | 34.50 | 2.75 | 60.00 | | 0,125 | 25.00 |
| FN036 | PG36 | 36.00 | 43.00 | 3.50 | 70.00 | | 0,140 | 25.00 |
| FN048 | PG48 | 48.00 | 54.50 | 3.25 | 80.00 | | 0,223 | 25.00 |