



POLYAMIDE CORRUGATED CONDUIT, GRAY


- Polyamide PA6 material
- Polyamide annular corrugated flexible conduit, light, it is extremely flexible with a very low bending radius
- Resistant to ageing and weathering good oils and acids
- Halogen-free
- Self Extinguishing flame retardant UL94 V2-HB
- Color : Gray

IP55

-40 C

+120 C

Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/m)	In Pack (m)
FN705		5.00	8.00	1.50	20.00			100.00
FN707	PG7	6.50	10.00	1.75	20.00		0,016	100.00
FN709		8.50	12.00	1.75	20.00		0,025	100.00
FN710	PG9	10.00	13.00	1.50	25.00		0,025	100.00
FN712	PG11	12.00	16.00	2.00	30.00		0,032	50.00
FN714	PG13.5	14.00	19.00	2.50	35.00		0,048	50.00
FN717	PG16	17.00	21.00	2.00	40.00		0,063	50.00
FN719		19.50	24.00	2.75	45.00			50.00
FN723	PG21	23.00	29.00	3.00	50.00		0,090	50.00
FN726		26.00	31.00	2.50	55.00		0,102	25.00
FN729	PG29	29.00	34.50	2.75	60.00		0,125	25.00
FN736	PG36	36.00	43.00	3.50	70.00		0,140	25.00
FN748	PG48	48.00	54.50	3.25	80.00		0,204	25.00