


FLEXIBLE STEEL CONDUIT PVC COATED GRAY



- Flexible conduit of galvanized steel with plain PVC oversheath
- Sheet thickness : 0,25mm
- Compression strength : 750N
- Impact strength : 2J
- The PVC oversheath has high resistance to abrasion, diluted acids, oils
- Resistance to weathering
- Using L3000 fittings the protection degree is IP66
- Color : Gray

| | | |
|------|-------|-------|
| IP57 | -15 C | +70 C |
|------|-------|-------|

Technical Details



| Product Code | Size I | A | B | C | D | E | Net Weight (kg/m) | In Pack (m) |
|--------------|--------|--------|--------|------|--------|---|-------------------|-------------|
| BS710 | 1/4" | 10.00 | 14.50 | 2.25 | 50.00 | | 0,101 | 100.00 |
| BS713 | 3/8" | 13.00 | 18.00 | 2.50 | 50.00 | | 0,124 | 50.00 |
| BS716 | 1/2" | 16.00 | 21.00 | 2.50 | 65.00 | | 0,201 | 50.00 |
| BS721 | 3/4" | 21.00 | 26.00 | 2.50 | 75.00 | | 0,275 | 50.00 |
| BS726 | 1" | 26.00 | 32.00 | 3.00 | 100.00 | | 0,467 | 50.00 |
| BS735 | 1 1/4" | 35.00 | 41.00 | 3.00 | 125.00 | | 0,682 | 30.00 |
| BS740 | 1 1/2" | 40.00 | 47.00 | 3.50 | 150.00 | | 0,751 | 30.00 |
| BS752 | 2" | 51.00 | 59.00 | 4.00 | 175.00 | | 1,017 | 20.00 |
| BS763 | 2 1/2" | 63.00 | 73.00 | 5.00 | 200.00 | | 1,871 | 10.00 |
| BS778 | 3" | 78.00 | 89.00 | 5.50 | 225.00 | | 2,051 | 10.00 |
| BS802 | 4" | 102.00 | 114.00 | 6.00 | 275.00 | | 2,285 | 10.00 |