



## FLEXIBLE STEEL CONDUIT PVC COATED GRAY

- Flexible conduit of galvanized steel with plain PVC oversheath
- Sheet thickness : 0,25mm
- Compression strength : 750N
- Impact strength : 2J
- The PVC oversheath has high resistance to abrasion, diluted acids, oils
- Resistance to weathering
- Using L3000 fittings the protection degree is IP66
- Color : Gray

IP57	-15 C	+70 C
------	-------	-------

### Technical Details



Product Code	Size I	A	B	C	D	E	Net Weight (kg/m)	In Pack (m)
BS710	1/4"	10.00	14.50	2.25	50.00		0,101	100.00
BS713	3/8"	13.00	18.00	2.50	50.00		0,124	50.00
BS716	1/2"	16.00	21.00	2.50	65.00		0,201	50.00
BS721	3/4"	21.00	26.00	2.50	75.00		0,275	50.00
BS726	1"	26.00	32.00	3.00	100.00		0,467	50.00
BS735	1 1/4"	35.00	41.00	3.00	125.00		0,682	30.00
BS740	1 1/2"	40.00	47.00	3.50	150.00		0,751	30.00
BS752	2"	51.00	59.00	4.00	175.00		1,017	20.00
BS763	2 1/2"	63.00	73.00	5.00	200.00		1,871	10.00
BS778	3"	78.00	89.00	5.50	225.00		2,051	10.00
BS802	4"	102.00	114.00	6.00	275.00		2,285	10.00