

Металлорукав В Пвх Изоляции И В Оплетке Из Оцинкованной Стали




IP43

-15 C

+70 C

Технические характеристики



Код продукта	Размер I	A	B	C	D	E	Вес нетто (kg/м)	Количество в
BSX008	5/16"	8.00	13.00				0,191	100.00
BSX010	1/4"	10.00	15.00				0,207	50.00
BSX013	3/8"	13.00	18.00				0,284	50.00
BSX016	1/2"	16.00	22.00				0,386	50.00
BSX021	3/4"	21.00	29.00				0,394	50.00
BSX026	1"	26.00	32.00				0,888	25.00
BSX035	1 1/4"	35.00	43.00				0,618	25.00
BSX040	1 1/2"	40.00	50.00				0,915	25.00
BSX052	2"	51.00	63.00				0,971	25.00
BSX063	2 1/2"	63.00	79.00					10.00
BSX078	3"	78.00	94.00					10.00
BSX102	4"	102.00	118.00					5.00
BSX510	1/4"	10.00	14.00				0,207	50.00
BSX513	3/8"	13.00	17.00				0,284	50.00
BSX521	3/4"	21.00	28.00				0,394	50.00
BSX526	1"	26.00	33.00				0,888	25.00
BSX552	2"	51.00	63.00				0,971	25.00



"Your Conduit Partner"

