

## FLEXIBLE CONDUIT, STEEL HIGH TEMPERATURE, STAINLESS BRAIDED



|      |       |        |
|------|-------|--------|
| IP42 | -40 C | +150 C |
|------|-------|--------|

### Технические характеристики



| Код продукта | Размер I | A      | B      | C | D | E | Вес нетто (kg/м) | Количество в |
|--------------|----------|--------|--------|---|---|---|------------------|--------------|
| BNTX008      | 5/16"    | 8.00   | 13.00  |   |   |   |                  | 50.00        |
| BNTX010      | 1/4"     | 10.00  | 15.00  |   |   |   | 0,201            | 50.00        |
| BNTX013      | 3/8"     | 13.00  | 18.00  |   |   |   | 0,257            | 50.00        |
| BNTX016      | 1/2"     | 16.00  | 22.00  |   |   |   | 0,343            | 50.00        |
| BNTX021      | 3/4"     | 21.00  | 27.00  |   |   |   |                  | 50.00        |
| BNTX026      | 1"       | 26.00  | 34.00  |   |   |   | 0,487            | 25.00        |
| BNTX035      | 1 1/4"   | 35.00  | 43.00  |   |   |   |                  | 25.00        |
| BNTX040      | 1 1/2"   | 40.00  | 49.00  |   |   |   |                  | 25.00        |
| BNTX052      | 2"       | 52.00  | 60.00  |   |   |   |                  | 25.00        |
| BNTX063      | 2 1/2"   | 63.00  | 76.00  |   |   |   |                  | 25.00        |
| BNTX078      | 3"       | 78.00  | 91.00  |   |   |   |                  | 15.00        |
| BNTX102      | 4"       | 102.00 | 113.00 |   |   |   |                  | 10.00        |