


Металлорукав В Пвх Изоляции И В Оплетке Из Нержавеющей Стали



| | | |
|------|-------|-------|
| IP43 | -15 C | +70 C |
|------|-------|-------|

Технические характеристики



| Код продукта | Размер I | A | B | C | D | E | Вес нетто (kg/м) | Количество в |
|--------------|----------|--------|--------|---|---|---|------------------|--------------|
| BSXS008 | 5/16" | 8.00 | 13.00 | | | | | 100.00 |
| BSXS010 | 1/4" | 10.00 | 15.00 | | | | 0,188 | 50.00 |
| BSXS013 | 3/8" | 13.00 | 18.00 | | | | 0,288 | 50.00 |
| BSXS016 | 1/2" | 16.00 | 22.00 | | | | 0,402 | 50.00 |
| BSXS021 | 3/4" | 21.00 | 29.00 | | | | 0,537 | 50.00 |
| BSXS026 | 1" | 26.00 | 32.00 | | | | 0,545 | 25.00 |
| BSXS035 | 1 1/4" | 35.00 | 43.00 | | | | | 25.00 |
| BSXS040 | 1 1/2" | 40.00 | 50.00 | | | | | 25.00 |
| BSXS052 | 2" | 52.00 | 63.00 | | | | | 20.00 |
| BSXS063 | 2 1/2" | 63.00 | 79.00 | | | | | 10.00 |
| BSXS078 | 3" | 78.00 | 94.00 | | | | | 10.00 |
| BSXS102 | 4" | 102.00 | 118.00 | | | | | 5.00 |