

## Металлорукав В Пвх Изоляции И В Оплетке Из Нержавеющей Стали




IP43

-15 C

+70 C

### Технические характеристики



| Код продукта | Размер I | A      | B      | C | D | E | Вес нетто (kg/м) | Количество в |
|--------------|----------|--------|--------|---|---|---|------------------|--------------|
| BSXS008      | 5/16"    | 8.00   | 13.00  |   |   |   |                  | 100.00       |
| BSXS010      | 1/4"     | 10.00  | 15.00  |   |   |   | 0,188            | 50.00        |
| BSXS013      | 3/8"     | 13.00  | 18.00  |   |   |   | 0,288            | 50.00        |
| BSXS016      | 1/2"     | 16.00  | 22.00  |   |   |   | 0,402            | 50.00        |
| BSXS021      | 3/4"     | 21.00  | 29.00  |   |   |   | 0,537            | 50.00        |
| BSXS026      | 1"       | 26.00  | 32.00  |   |   |   | 0,545            | 25.00        |
| BSXS035      | 1 1/4"   | 35.00  | 43.00  |   |   |   |                  | 25.00        |
| BSXS040      | 1 1/2"   | 40.00  | 50.00  |   |   |   |                  | 25.00        |
| BSXS052      | 2"       | 52.00  | 63.00  |   |   |   |                  | 20.00        |
| BSXS063      | 2 1/2"   | 63.00  | 79.00  |   |   |   |                  | 10.00        |
| BSXS078      | 3"       | 78.00  | 94.00  |   |   |   |                  | 10.00        |
| BSXS102      | 4"       | 102.00 | 118.00 |   |   |   |                  | 5.00         |