


FLEXIBLE CONDUIT, STEEL HIGH TEMPERATURE, STAINLESS BRAIDED



| | | |
|------|-------|--------|
| IP42 | -40 C | +150 C |
|------|-------|--------|

Технически характеристики



| Код продукта | Размер I | A | B | C | D | E | Вес нетто (kg/м) | Количество в |
|--------------|----------|--------|--------|---|---|---|------------------|--------------|
| BNTX008 | 5/16" | 8.00 | 13.00 | | | | | 50.00 |
| BNTX010 | 1/4" | 10.00 | 15.00 | | | | 0,201 | 50.00 |
| BNTX013 | 3/8" | 13.00 | 18.00 | | | | 0,257 | 50.00 |
| BNTX016 | 1/2" | 16.00 | 22.00 | | | | 0,343 | 50.00 |
| BNTX021 | 3/4" | 21.00 | 27.00 | | | | | 50.00 |
| BNTX026 | 1" | 26.00 | 34.00 | | | | 0,487 | 25.00 |
| BNTX035 | 1 1/4" | 35.00 | 43.00 | | | | | 25.00 |
| BNTX040 | 1 1/2" | 40.00 | 49.00 | | | | | 25.00 |
| BNTX052 | 2" | 52.00 | 60.00 | | | | | 25.00 |
| BNTX063 | 2 1/2" | 63.00 | 76.00 | | | | | 25.00 |
| BNTX078 | 3" | 78.00 | 91.00 | | | | | 15.00 |
| BNTX102 | 4" | 102.00 | 113.00 | | | | | 10.00 |