


Infos of VSXFF :



- IP67
- MIN -20
- MAX 80
- CERT
- VSXFF

**EX PROOF FLEXIBLE CONDUIT**

- ▶ Stainless steel core (AISI316L)
- ▶ Fittings and braiding wire are made of stainless steel AISI304
- ▶ Extremely small bending radius
- ▶ High flexibility
- ▶ Female - Female
- ▶ ATEX
- ▶ II 2G Ex e IIC Gb ; I M2
- ▶ II 2D Ex tb IIIC Db, IP66/67



Sizes & Prices :

Product Code	Size	Size	A (mm)	B (mm)	C (mm)	D (mm)	Meters in Pack (M)	Net Weight (kg/M)
<b>VSX816-0100 FF</b>	NPT 1/2"	NPT 1/2"	16.00	24.00	4.00	1000.00		0,000

Accessories :

EX PROOF FLEXIBLE CONDUIT MALE FEMALE



**VSXMF**

EX PROOF FLEXIBLE CONDUIT

EX-PROOF JUNCTION BOX Exd



**V2800**

EX-PROOF JUNCTION BOX Exd

EX-PROOF REDUCER, POLYAMIDE, BLACK



**V1600**

EX-PROOF REDUCER, POLYAMIDE, BLACK

EXPROOF STAINLESS STEEL PLUG



**V7300**

EXPROOF STAINLESS STEEL PLUG