


Infos of VSXMM :



- ☁️
- IP67
- MIN
- 20
- MAX
- 80
- CERT
- VSXMM

EX PROOF FLEXIBLE CONDUIT

- ▶ Stainless steel core (AISI316L)
- ▶ Fittings and braiding wire are made of stainless steel AISI304
- ▶ Extremely small bending radius
- ▶ High flexibility
- ▶ Male – Male
- ▶ ATEX
- ▶ II 2G Ex e IIC Gb ; I M2
- ▶ II 2D Ex tb IIIC Db, IP66/67



Sizes & Prices :

Product Code	Size	Size	A (mm)	B (mm)	C (mm)	D (mm)	Meters in Pack (M)	Net Weight (kg/M)
VSX816-0050 MM	NPT 1/2"	NPT 1/2"	16.00	24.00	4.00	500.00		0,000
VSX816-0100 MM	NPT 1/2"	NPT 1/2"	16.00	24.00	4.00	1000.00		0,000
VSX816-0150 MM	NPT 1/2"	NPT 1/2"	16.00	24.00	4.00	1500.00		0,000
VSX816-0200 MM	NPT 1/2"	NPT 1/2"	16.00	24.00	4.00	2000.00		0,000
VSX816-0300 MM	NPT 1/2"	NPT 1/2"	16.00	24.00	4.00	3000.00		0,000

Accessories :

EX-PROOF REDUCER NIPPLE, BRASS



V6760

EX-PROOF REDUCER NIPPLE, BRASS

EX-PROOF NIPPLE, BRASS



V6700

EX-PROOF NIPPLE, BRASS

EX-PROOF FLUORESCENT LIGHTING FIXTURES 2x36W



V9500

Ex Zone II

EX-PROOF SEALING FITTING, HORIZONTAL, EZS



V4160

EX-PROOF SEALING FITTING, HORIZONTAL, EZS