

EX PROOF FLEXIBLE CONDUIT




- Stainless steel core (AISI316L)
- Fittings and braiding wire are made of stainless steel SS304
- Extremely small bending radius
- High flexibility
- Male – Male
- ATEX
- II 2G Ex e IIC Gb ; I M2
- II 2D Ex tb IIIC Db, IP66/67

IP67

-20 C

+80 C

Технические характеристики



Код продукта	Размер I	Размер II	A	B	C	D	E	Вес нетто (кг/шт)	Количество в
VSX816-0050MM	NPT 1/2"	NPT 1/2"	12.00	24.00	4.00	500.00			
VSX816-0075MM	NPT 1/2"	NPT 1/2"	12.00	24.00	4.00	750.00			
VSX816-0100MM	NPT 1/2"	NPT 1/2"	12.00	24.00	4.00	1000.00			
VSX816-0150MM	NPT 1/2"	NPT 1/2"	12.00	24.00	4.00	1500.00			
VSX816-0200MM	NPT 1/2"	NPT 1/2"	12.00	24.00	4.00	2000.00			
VSX816-0300MM	NPT 1/2"	NPT 1/2"	12.00	24.00	4.00	3000.00			
VSX821-0050MM	NPT 3/4"	NPT 3/4"	15.00	22.00	3.50	500.00			
VSX821-0100MM	NPT 3/4"	NPT 3/4"	15.00	22.00	3.50	1000.00			
VSX821-0150MM	NPT 3/4"	NPT 3/4"	15.00	22.00	3.50	1500.00			
VSX826-0050MM	NPT 1"	NPT 1"	20.00	30.00	5.00	500.00		0,516	30.00