

EX-PROOF LIQUID-TIGHT CONNECTOR, SILOK TYPE

- нержавеющая сталь (316L)
- ATEX II 2GD Ex db IIC Gb ; Ex eb IIC Gb ; Ex tb IIIC Db, IP66/68



| | | |
|------|-------|--------|
| IP68 | -40 C | +100 C |
|------|-------|--------|

Технические характеристики



| Код продукта | Размер I | A | B | C | D | E | Вес нетто (кг/шт) | Количество в |
|--------------|------------|-------|-------|-------|---|---|-------------------|--------------|
| V780413 | M20x1.5 | 13.00 | 4.00 | 12.00 | | | | |
| V780416 | M20x1.5 | 16.00 | 4.00 | 12.00 | | | 0,103 | 20.00 |
| V780421 | M25x1.5 | 21.00 | 10.00 | 18.00 | | | | |
| V780426 | M32x1.5 | 26.00 | 14.00 | 24.00 | | | | |
| V780435 | M40x1.5 | 35.00 | 22.00 | 32.00 | | | | |
| V780440 | M50x1.5 | 40.00 | 26.00 | 35.00 | | | | |
| V780813 | NPT 1/2" | 13.00 | 4.00 | 12.00 | | | | |
| V780816 | NPT 1/2" | 16.00 | 4.00 | 12.00 | | | | |
| V780821 | NPT 3/4" | 21.00 | 10.00 | 18.00 | | | | |
| V780826 | NPT 1" | 26.00 | 14.00 | 24.00 | | | | |
| V780835 | NPT 1 1/4" | 35.00 | 22.00 | 32.00 | | | | |
| V780840 | NPT 1 1/2" | 40.00 | 26.00 | 35.00 | | | | |